

OM3 Duplex LC/LC Fiber Jumper 3 Meter



PART NUMBER: FJ-LC-LC-OM303M

NOTES

CABLE SHEATH MATERIAL WITH LSZH OR OFNP OR OFNR, FIBER TYPE IS OS2 OS OM3, OM4 FIBER; CABLE CROSS-SECTION PLEASE SEE VIEW C-C.

CABLE ATTENUATION 0.45B/KM @ 1310NM AND 0.3DB/KM @ 1500NM FOR SINGLE MODE CABLE; 3.5DB/KM @ 850NM AND 1.5DB/KM @ 1300NM FOR MULTI-MODE CABLE;

APC POLISHED FOR SINGLE MODE, UPC POLISHED FOR SINGLE MODE, PC POLISHED FOR MULTI-MODE CABLE;

CONNECTOR INSERTION STANDARD LOSS

MULTI-MODE:	IL \leq 0.20DB @ 850NM & 1300NM RL \geq 30DB @ 850NM & 1300NM
SINGLE-MODE UPC:	IL \leq 0.30DB @ 1310NM & 1550NM RL \geq 50DB @ 1310NM & 1550NM
SINGLE-MODE APC:	IL \leq 0.30DB @ 1310NM & 1550NM RL \geq 60DB @ 1310NM & 1550NM

ROHS COMPLIANT

TOLS.

~20MM:	+/- 0.2MM
OVER 20MM TO 60MM:	+/- 0.4MM
OVER 60MM:	+/- 0.8MM
ANGLES:	+/- 1 DEGREE

